

## SBO/KBO - ROUND STRANDED COPPER CABLES



### Construction and Application:

These cables are manufactured out of wires that have a stronger diameters than 0,10 mm. They can be used for all applications where you need more mechanical stability than higher flexibility.

### Technical Data:

**Material:** 0,15 mm - 0,85 mm annealed Cu ETP1 wires \*uncoated or tinned.

**Delivery:** plastic reels, in rings, on spools or wooden drums.

UNCOATED Part-No	TINNED Part-No	Cross sec. mm <sup>2</sup>	Construction		Weight kg/100m
			wire dia. mm	outer dia. mm	
SBO-0060	KBO-0060	6	acc. to customers' wishes	4	6
SBO-0100	KBO-0100	10		4,5	10
SBO-0160	KBO-0160	16		5,8	16
SBO-0250	KBO-0250	25		7,5	25
SBO-0350	KBO-0350	35		9	35
SBO-0500	KBO-0500	50		11	50
SBO-0700	KBO-0700	70		13	70
SBO-0950	KBO-0950	95		15	95
SBO-1200	KBO-1200	120		17	120
SBO-1500	KBO-1500	150		19	150
SBO-1850	KBO-1850	185		21	185
SBO-2400	KBO-2400	240		22,5	240
SBO-3000	KBO-3000	300		25,5	300
SBO-4000	KBO-4000	400		33,5	400
SBO-5000	KBO-5000	500	38	500	