



## ST/KT - EARTHING TAPES WITH PRESSED CONTACT AREAS

### Construction and Application:

These connectors are manufactured from highly flexible tapes, which are braided from annealed Cu-ETP1 wires, and solderless contact areas pressed from seamless Cu-ETP tubes. The braided tapes and tubes are of same analysis and conductivity. No additives are used at the process of pressing the contact areas. Applicable as earthing tape where needed and everywhere as component for current transfer.



### Technical Data:

**Material:** 0,07 - 0,20 mm annealed Cu-ETP wires , uncoated or tinned.

- Non-insulated or insulated (shrinking tubes, PVC, silicone tubes etc.)

**Contact Areas:** Seamless Cu-ETP tube ; uncoated - tinned or silver coated, solderless pressed.

UNCOATED Part-No	TINNED Part-No	Cross sec. mm <sup>2</sup>	DIMENSIONS				Current- load ampere
			W mm	L1 mm	L mm	d mm	
ST-004	KT-004	4	8	12	acc. to customers' wishes	acc. to customers' wishes	15
ST-006	KT-006	6	10	16			40
ST-008	KT-008	8	12	16			60
ST-010	KT-010	10	14	18			75
ST-014	KT-014	14	16	18			95
ST-016	KT-016	16	16	20			120
ST-021	KT-021	21	20	20			135
ST-025	KT-025	25	20	23			150
ST-035	KT-035	35	25	25			195
ST-050	KT-050	50	30	30			250
ST-070	KT-070	70	35	35			290
ST-095	KT-095	95	40	40			330
ST-120	KT-120	120	40	40			420

